

Claims

What is claimed is:

- [c1] A method to support access control checks in a directory server with a chaining backend, comprising:
- binding a user to a multiplexer;
 - forwarding an authentication sequence from the multiplexer to a first remote server;
 - binding the user to the first remote server;
 - authenticating the user if binding to the first remote server is successful;
 - binding the multiplexer as a special user to a second remote server, wherein the second remote server holds target data;
 - sending an operation and an original user identity from the user to the multiplexer;
 - and
 - forwarding the operation from the multiplexer to the second remote server.
- [c2] The method of claim 1, further comprising:
- retrieving an access control information statement from an access control list stored on the second remote server; and
 - evaluating the operation by the second remote server using the access control statement of the user.
- [c3] The method of claim 2, wherein the access control information statement is stored as an attribute of an entry on the second remote server.
- [c4] The method of claim 3, wherein the access control information statement comprises a target and an access control rule.

Continued

- [c5] The method of claim 1, further comprising:
retrieving an access control information statement from an access control list
stored on the multiplexer; and
evaluating the operation by the multiplexer using the access control statement of
the user.
- [c6] The method of claim 5, wherein the access control information statement is stored
as an attribute of an entry on the multiplexer.
- [c7] The method of claim 6, wherein the access control information statement
comprises a target and an access control rule.
- [c8] The method of claim 1, wherein forwarding the authentication sequence to the first
remote server occurs when a realm value sent in a digest challenge is not
interpreted by the directory server, a target host name field of a digest response is
not checked by the directory server, and the first remote server is part of a
common realm.
- [c9] The method of claim 1, wherein the operation comprises an internal operation
portion and an external operation portion.
- [c10] The method of claim 9, further comprising:
chaining the internal operation portion based on an identity of a component issuing
the internal operation.
- [c11] The method of claim 2, further comprising:
enabling retrieval of the access control information statement on a remote server
basis.

- [c12] The method of claim 2, further comprising:
disabling retrieval of the access control information statement on a remote server basis.
- [c13] The method of claim 6, further comprising:
retrieving the entry to evaluate an access control list on the multiplexer.
- [c14] The method of claim 13, wherein the entry comprises a user.
- [c15] The method of claim 13, wherein the entry comprises a group.
- [c16] A computer system to support access control checks in a directory server with a chaining backend, comprising:
a processor;
a memory; and
software instructions stored in the memory for enabling the computer system under control of the processor, to perform:
binding a user to a multiplexer;
forwarding an authentication sequence from the multiplexer to a first remote server;
binding the user to the first remote server;
authenticating the user if binding to the first remote server is successful;
binding the multiplexer as a special user to a second remote server, wherein the second remote server holds target data;
sending an operation and an original user identity from the user to the multiplexer; and
forwarding the operation from the multiplexer to the second remote server.

[c17] The computer system of claim 16, wherein the software instructions further comprise instructions to perform:

retrieving an access control information statement from an access control list stored on the second remote server; and
evaluating the operation by the second remote server using the access control statement of the user.

[c18] The computer system of claim 16, wherein the software instructions further comprise instructions to perform:

retrieving an access control information statement from an access control list stored on the multiplexer; and
evaluating the operation by the multiplexer using the access control statement of the user.

[c19] An apparatus to support access control checks in a directory server with a chaining backend, comprising:

means for binding a user to a multiplexer;
means for forwarding an authentication sequence from the multiplexer to a first remote server;
means for binding the user to the first remote server;
means for authenticating the user if binding to the first remote server is successful;
means for binding the multiplexer as a special user to a second remote server, wherein the second remote server holds target data;
means for sending an operation and an original user identity from the user to the multiplexer; and
means for forwarding the operation from the multiplexer to the second remote server.

[c20] The apparatus of claim 19, further comprising:
means for retrieving an access control information statement from an access control list stored on the second remote server; and
means for evaluating the operation by the second remote server using the access control statement of the user.

[c21] The apparatus of claim 19, further comprising:
means for retrieving an access control information statement from an access control list stored on the multiplexer; and
means for evaluating the operation by the multiplexer using the access control statement of the user.